

NAG1-648

DEPARTMENT OF MECHANICAL ENGINEERING AND MECHANICS  
COLLEGE OF ENGINEERING AND TECHNOLOGY  
OLD DOMINION UNIVERSITY  
NORFOLK, VIRGINIA 23508

UNSTEADY HYBRID VORTEX TECHNIQUE FOR TRANSONIC VORTEX  
FLOWS AND FLUTTER APPLICATIONS

1N-02  
63733  
p. 34

By

Osama A. Kandil, Principal Investigator

Progress Report  
For the period February 16, 1986 to October 15, 1986

Prepared for the  
National Aeronautics and Space Administration  
Langley Research Center  
Hampton, VA 23665

Under  
Research Grant NAG-1-648  
Dr. Samuel Bland, Technical Monitor  
Unsteady Aerodynamics Branch  
Loads and Aeroelasticity Division

(NASA-CR-180337) UNSTEADY HYBRID VORTEX  
TECHNIQUE FOR TRANSONIC VORTEX FLOWS AND  
FLUTTER APPLICATIONS Progress Report, 16  
Feb. - 15 Oct. 1986 (Old Dominion Univ.)  
34 p Avail: NTIS HC A03/MF A01 CSCL 01A G3/02

N87-26859

Unclas  
0063733

November 1986

DEPARTMENT OF MECHANICAL ENGINEERING AND MECHANICS  
COLLEGE OF ENGINEERING AND TECHNOLOGY  
OLD DOMINION UNIVERSITY  
NORFOLK, VIRGINIA 23508

UNSTEADY HYBRID VORTEX TECHNIQUE FOR TRANSONIC VORTEX  
FLOWS AND FLUTTER APPLICATIONS

By

Osama A. Kandil, Principal Investigator

Progress Report  
For the period February 16, 1986 to October 15, 1986

Prepared for the  
National Aeronautics and Space Administration  
Langley Research Center  
Hampton, VA 23665

Under  
Research Grant NAG-1-648  
Dr. Samuel Bland, Technical Monitor  
Unsteady Aerodynamics Branch  
Loads and Aeroelasticity Division

Submitted by the  
Old Dominion University Research Foundation  
P.O. Box 6369  
Norfolk, VA 23508

November 1986

## Unsteady Hybrid Vortex Technique for Transonic Vortex Flows and Flutter Applications

Osama A. Kandil

This report covers the progress of research work performed under this grant in the period of February 16, 1986 to October 15, 1986. During this period of eight months, the following tasks have been accomplished:

### 1. Integral Equation Method of Full Potential Equations

The integral equation method has been extended to treat transonic flows around airfoils. This is achieved by adding a volume integral term (corresponding to the full compressibility effect) to the classical surface integral solution. The gradient terms in the volume integral term are calculated by using mixed type differencing which is consistent with the mixed nature of the transonic flow. The solution is obtained through successive iteration cycles for subcritical flows. In addition and for transonic flows, mixed type differencing is used and the Rankine-Hugoniot relations are satisfied across the captured shock. Moreover, shock panels are explicitly introduced and fitted to sharpen the captured shock.

The method is applied to airfoils in subcritical and critical flows and the results are in good agreement with the experimental data and the finite-difference solutions of the full-potential and Euler equations. The method has been applied earlier to transonic vortex-dominated three-dimensional flows using a low-order distribution of vortex panels. Currently the method is extended to solve for unsteady transonic flows around pitching airfoils and to solve for the steady and unsteady transonic flows around three-dimensional wings.

The following papers have been published or submitted for presentations (copies are attached to this report):

- a. "Transonic Flow Computation Using the Integral Solution of the Full Potential Equations," Kandil, O. A. and Hong, H., submitted for presentation at the AIAA Fluid and Plasma Dynamics Conference, Honolulu, Hawaii, June 8-10, 1987.

- b. "Finite-Volume and Integral-Equation Techniques for Transonic and Supersonic Vortex-Dominated Flows," Kandil, O. A., Chuang, A. and Chu, L-C., ICAS-86-1.5.4, London, England, September 7-12, 1986, pp. 629-640 (Vol. 1).
  - c. "Transonic Vortex Flow Past Delta Wings-Integral Equation Approach," AIAA Journal, Vol. 24, No. 11, 1986, pp. 1729-1736.
2. Euler Equations Solution Using Central-Differencing Finite Volume Solver with Second and Fourth Order Dissipation Terms

During this period, we have implemented Jameson's Central-Differencing Finite Volume Method, which uses Runge Kutta time stepping with second and fourth order explicit dissipation terms, into two computer codes to solve for vortex dominated flows over a wide range of Mach numbers which includes subsonic, transonic and supersonic regimes.

The first computer code solves for the supersonic vortex-dominated flows which is an exact conical flow for steady inviscid problems. The unsteady Euler equations are used to study conical supersonic vortex-dominated flows around delta wings with sharp and round edges. For sharp edges, separated flow solutions have always been obtained while for round edges, separated and attached flow solutions have been obtained. The solution for round edges is dependent upon the level of numerical dissipations and the grid fineness. We are the first to conclusively show the solution dependence upon the numerical dissipation for round edges. Recently, we have shown two additional parameters upon which the solution depends. These are the total pressure loss due to the entropy production and the accuracy of enforcing the boundary conditions.

The second computer code solves for the three-dimensional flows in subsonic, transonic and supersonic flows. The code is fully vectorized and is very efficient (For 130,000 grid points, it takes 3,000 CRU for 900 iteration cycles until convergence -- average residuals of  $10^{-4}$  - on the VPS 32). The code has been used to solve for transonic and subsonic vortex-dominated flows and for supersonic vortex-dominated flows as well. The results compare well with the experimental results at the chord stations downstream of the 18% chord station with 130,000 grid points. Fine grids (300,000 points) are being tested.

Work is underway to solve for the unsteady pitching and rolling oscillations with time accurate schemes.

The results of this work have been reported in the following papers (copies are attached with this report):

- a. "Numerical Dissipation Effects in Finite-Volume Euler Solutions for Conical Vortex-Dominated Flows," Kandil, O. A. and Chuang, A., Springer Verlag, Computational Mechanics, Theory and Applications, Edited by G. Iagawa and S. Atluri, Tokyo, Japan, May 1986, pp. XI57-XI.64 (Vol. II).
- b. "Influence of Numerical Dissipation in Computing Supersonic Vortex-Dominated Flows," Kandil, O. A. and Chuang, A., AIAA 86-1073, May 1986. Accepted for publication in AIAA Journal.
- c. "State of the Art of Computational Vortex Flows," Kandil, O. A. and Chuang, A., SIAM National Meeting, Boston, Mass., July 1986.
- d. "Finite-Volume Euler and Navier-Stokes Solvers for Three-Dimensional and Conical Vortex Flows Over Delta Wings," Kandil, O. A. and Chuang, A., AIAA 87-041, January 1987.

### 3. Presentations and Briefings:

The P.I. has given three presentations and briefings at the UAB-NASA Langley Research Center:

- a. Briefing to Dr. Eligh Turner, Wright Patterson AFB, on the Vortex-Dominated Flow work.
- b. Briefing during Division and Directorate Annual Review of the UAB Research work.
- c. Presentation to McDonald Douglas visitors to NASA Langley Research Center on the Steady and Unsteady Vortex-Dominated Flow research work, September 17, 1986.

#### 4. Organizing and Chairing Sessions on Vortex Dominated Flows

The P.I. has organized and chaired the following sessions in the vortex flow area:

- a. "Vortex Flows," AIAA 24th Aerospace Sciences Meeting, January 1986.
- b. "Computational Vortex Flows," SIAM National Meeting, July 1986.
- c. "Vortex Dominated Flows I & II," AIAA 25th Aerospace Sciences Meeting, January 1987.

# Abstract Submittal Form

Print or type all information

I wish to submit an abstract for (conference/meeting): Fluid and Plasma Dynamics Conference

Place: Honolulu, Hawaii

Date: June 8-10, 1987

Session/organizer (this information appears in the call): Dr. Helen Reed, Arizona State

## Reminders:

- 1/ AIAA has first publication rights to all papers presented at its meetings. Manuscripts accepted for the meeting will be evaluated for publication in the appropriate AIAA publication, if the author requests it. If a Progress Series book is planned, papers from relevant sessions will be held for the book.
- 2/ Authors must inform each organizer if abstract is submitted to more than one session topic organizer.
- 3/ All program participants and authors will be charged a registration fee (AIAA member rate) at the meeting.
- 4/ Authors of accepted papers will be expected to submit a photo-ready manuscript 8 weeks before a meeting. Authors desiring journal publication should send 4 copies of their photo-ready manuscript directly to the Editor in Chief of the journal of their choice (see inside front cover of each journal for correct address), along with a covering letter, before the meeting, if they wish to accelerate the review procedure. Government Program Monitors/Security Officers should be alerted as soon as authors receive formal acceptance of their paper.

Paper title (this title will be published in the Program):

Transonic Flow Computation Using the Integral Solution of the Full Potential Equation.

Author/s' name and title, AIAA membership grade, company, full mailing address, telephone number:

1 Author presenting paper

Prof. Osama A. Kandel  
Dept. of Mechanical Engineering  
and Mechanics  
Old Dominion Univ., Norfolk, VA. 23508

2

Mr. Hong Hu  
Ph.D. Graduate Research Assistant  
(Same Address as author ①)

3

4

Abstract due date: Nov. 17, 1986

Draft of paper included? ☐ Yes ☒ No Extended Abstract is included

Similar results been presented or published elsewhere? ☐ Yes ☒ No

Concise statement of problem (its genesis and objective covered):

Currently, the integral solution of the full potential equation for transonic flows is receiving a growing attention and in particular for unsteady flows. The integral solution is computationally efficient as compared to the finite difference solutions of the full potential equation and Euler equations. For field boundary conditions are automatically satisfied and the computational domain is much smaller than that required for the finite difference equation.

Scope and methods of approach, with statement of contribution to the state-of-the-art or an application of existing analytical techniques and theories to a problem:

A shock capturing - shock fitting technique has been developed by using the integral solution of the full potential equation. The full compressibility is found from a volume integral term which uses mixed type differencing. Rankine Hugenot equations are used to calculate the properties across the shock and the shock is sharpened by using shock panels. The technique is applied to unsteady pitching airfoils.

Summary of important conclusions: The integral solutions have shown good agreement with the experimental data and the finite difference solutions of the FP and Euler Equations. It is capable of capturing sharp shocks within a few iteration steps. Addition of shock panels further sharpens the shocks.

Statement of data used to substantiate conclusions, and freehand sketches of major figures to be used (no more than two typed pages):

See the Comparisons in Figures ② - ⑥.

## Extended Abstract

### Transonic Flow Computation Using the Integral Solution<sup>†</sup> of the Full Potential Equation

Osama A. Kandil\* and Hong Hu\*\*  
Department of Mechanical Engineering and Mechanics  
Old Dominion University, Norfolk, VA 23508

#### Abstract

The well developed surface panel method is extended by adding a volume integral term allowing the calculation of the full effect of compressibility. The full effect of compressibility is calculated by using mixed type finite difference scheme consistent with the mixed nature of transonic flow. The solution is obtained through successive iteration cycles for subcritical flows and for critical flows the solution is obtained through satisfying the Rankine-Hugoniot relations across the captured shock in addition to the successive iteration cycles. Shock panels are introduced to sharpen the captured shock. The method is applied to airfoils in subcritical and critical flows and the results are in good agreement with the experimental data and finite-difference solutions of the full-potential and Euler equations.

---

† This research work is supported by NASA Langley under Grant No. NAG-1-S91.

\* Professor, AIAA member.

\*\* Ph.D Graduate Research Assistant, AIAA member.

## 1. INTRODUCTION AND BACKGROUND

At the present time, computational inviscid flow prediction methods available to the aerodynamic designer can be divided into two types: first, the integral equation methods more commonly known as panel methods or field panel methods of which the first was that developed by Hess and Smith [1] and second, field methods (which encompass Finite-Difference, Finite-Volume and Finite-Element methods) which have been extensively developed for transonic flow following the work of Murman and Cole [2].

A brief review of the state of the art of computational transonic inviscid flows will be presented here.

### (a) Field Methods in Steady Inviscid Transonics

The research for inviscid transonics has been made in major three ways: (i) the transonic small-disturbance (TSD) formulation, (ii) full-potential (FP) formulation and (iii) Euler equation formulation which includes the rotationality effect.

The field methods of transonics are the new ones, having essentially started in 1970. Murman and Cole [2] were the first to achieve a stable transonic solution for the two-dimensional TSD equation by using the concept of type-dependent differencing. Soon after, this procedure was extended to three dimensional flows for swept-wing calculations by Ballhaus and Bailey [3] and wing-cylinder calculations by Bailey and Ballhaus [4]. At about this same time, numerical procedures for solving the transonic FP equation were being developed with suitable mapping procedures. Notable contributions are due to Stegar and Lomax [5] and Garabedian and Korn [6], both with nonconservative FP formulations for airfoil configurations. The first three-dimensional calculation (nonconservative) was introduced by Jameson [7] and was used to

solve the transonic flow about wings. Subsequently, a solution procedure for the conservative form of the FP equation was introduced by Jameson [8] and extended to three dimensions by Jameson and Caughey [9, 10].

Much of the recent work in steady transonic potential field methods has been devoted to finding better ways of solving the full potential equation in conservation form and to the development of more computationally efficient relaxation schemes, such as fully implicit approximate factorization (AF) or multigrid. Recently, several methods which use the strong conservative form of the unsteady Euler equation have been developed to solve steady and unsteady transonic flows. A typical method for steady, two-dimensional transonic flow is developed by Jameson [11]. Basic research involving the Euler formulation for steady transonic applications is currently increasing and is expected to continue to do so as the potential algorithms enter a more production-oriented research phase.

(b) Integral Equation Methods in Steady Inviscid Transonics

Although a great deal of progress has been made in solving nonlinear fluid flow problems by finite-difference methods, these methods have not yet proved to be easily adaptable to complex three-dimensional surfaces. The major technical obstacle to computing inviscid transonic flows about complete aircraft is the difficulty in generating suitable grids. More recently, the difficulties and relatively larger computation time associated with field methods prompted a number of workers to reconsider the application of integral equation methods to transonic flows.

Panel methods for subsonic and supersonic aerodynamic applications have been in use in the aerospace community since the 1960s and have become indispensable tools in aerodynamic analysis and design.

In the low-speed regime, methods which are directly or indirectly obtained from the Green's function solution (IEM) have been developed for steady and unsteady 3-D vortex flows. Existing methods of this type are the Nonlinear Discrete-Vortex methods [12-15], the Double-Panel methods [16-20], the Vortex-Panel method [21-22] and the Velocity-Potential-Panel method [23]. Flow compressibility has been accounted for by using the Prandtl-Glauert transformation, based on the free-stream Mach number.

Exact integral equation formulation of the 2-D subsonic full potential problem have been studied by Luu et al. [24] and Stricker [25]. However, these methods are not capable of dealing with flow with shocks.

Relatively little (compared with field methods) attention has been paid, so far, to integral equation methods for transonic flows. certain approximate IEM formulations of the transonic small-perturbation problem were studied already in the pre-computer era, notably by Oswatitsch [26] and Spreiter [27]. Computerized and extended versions of the approximate IEM were developed later by, amongst others, Norstrud [28], Crown [29] and Nixon [30]. It should be remarked that the approximate IEM's mentioned above, are all based on a special, partial-integration form of the integral equation for the transonic small-disturbance problem, which enables easy implementation of approximating assumptions on the decay of the perturbation velocity away from the body. The approximating assumptions on the decay of the perturbation velocity and the shock-fitting character of these methods are not considered to be competitive with FDM's.

Later, Piers and Slooff [31] developed a IEM based on transonic small-disturbance theory. Their method does not contain any approximating assumptions and, through the introduction of artificial viscosity and directional bias, has a shock-capturing capability similar to that of current FDM's.

The development of the numerical methods based on the full potential equation has been made during the last two years. Kandil and Yates [32] developed a IEM for steady transonic flows past delta wing, the results show that the method is promising and efficient. Oskam [33] developed a panel method for the full potential equation applied to multicomponent airfoils. This method is accomplished by adding a field distribution of source singularities to the conventional distribution of singularities over the boundaries of the field. At about the same time, Erickson and Strande [34] used Green's Third Identity as a means to extend panel method to non-linear potential flow, in which the concept of artificial density is employed and optimization technique is used to make sure the total compressibility is conserved. Later on, Sinclair [35] published an exact IEM for 2-D steady transonic flows, which is similar to Erickson's [34] method.

The study of these integral equation methods shows a very good potential for IEM to challenge widely used FD methods and to replace FD methods in some fields of potential transonic flows, but, the development of the IE method is far from complete. Therefore, it is a challenge task to develop transonic integral equation methods.

## 2. ADVANTAGES OF INTEGRAL EQUATION METHODS

The integral equation method has several advantages over the finite difference method. The IE approach involves evaluation of integrals, which is more accurate and simpler than the FD approach in which the accuracy depends on the grid size. In IE approach, grid refinement and high order source-vorticity and compressibility modeling can be used in order to increase the accuracy. Moreover, the IE method automatically satisfies the far-field boundary conditions as  $O(1/r)$  or  $O(1/r^2)$  and hence a small limited region

around the source of disturbance is needed. In FD method, grid points are needed over a large region around the source of disturbance and special treatment is required to satisfy the far-field boundary conditions. The IE method is computationally inexpensive, particularly for unsteady flows, and does not suffer from the artificial viscosity effects as compared to FD method for transonic-flow-shock-capturing.

### 3. FORMULATION

The work presented here is for steady, inviscid transonic flows around two-dimensional configurations.

#### (a) Differential Governing Equation and B.C.'s

The governing equations of the two-dimensional, steady, inviscid compressible flow are given by

Conservation Of Mass

$$(\rho^* \Phi_x^*)_{x^*} + (\rho^* \Phi_z^*)_{z^*} = 0 \quad (1)$$

Conservation of Energy

$$a_\infty^{*2} + \frac{\gamma-1}{2} V_\infty^{*2} = a^{*2} + \frac{\gamma-1}{2} (\Phi_x^{*2} + \Phi_z^{*2}) \quad (2)$$

Isentropic Gas equation

$$\rho^* / \rho_\infty^* = (a^{*2} / a_\infty^{*2})^{1/\gamma-1} \quad (3)$$

where  $\Phi^*$  is the total velocity potential,  $a^*$  is the speed of sound,  $\rho^*$  is the density,  $\gamma$  is the ratio of specific heats, and the subscript  $\infty$  refers to the freestream condition. Combining equations (2) and (3) and using  $V_\infty^*$ ,  $\rho_\infty^*$  and a length  $l$  ( $l$  is the chord of airfoil) as the reference parameters, we obtain the dimensionless equation for the density  $\rho$

$$\rho = [1 + \frac{\gamma-1}{2} M_\infty^2 (1 - \Phi_x^2 - \Phi_z^2)]^{\frac{1}{\gamma-1}} \quad (4)$$

where  $M_\infty$  is the freestream Mach number.

The dimensionless form of equation (1) is given by

$$\Phi_{xx} + \Phi_{zz} = G \quad (5)$$

where

$$G = -\frac{1}{\rho} (\rho_x \Phi_x + \rho_z \Phi_z) \quad (6)$$

The boundary conditions are given by

(i) Surface No-Penetration (kinematic) Condition

$$\bar{V} \cdot \bar{n}_g = 0 \quad \text{on } g(\bar{r}) = 0 \quad (7)$$

(ii) Kutta Condition

$$\Delta C_p \Big|_{TE} = 0 \quad (8)$$

(iii) Infinity Condition

$$\nabla \Phi \rightarrow 0 \quad \text{away from } g \quad (9)$$

where  $\bar{V}$  is total velocity vector,  $g(\bar{r}) = 0$  is body (airfoil) surface,  $C_p$  is pressure coefficient and TE refers to the trailing edge.

(b) Integral Equation Solution

The integral equation solution of Eq. (5) for a two-dimensional configuration is given in terms of the velocity field by

$$\begin{aligned} \bar{V}(x, z) = \bar{e}_\infty + \frac{1}{2\pi} \oint_g q_g(s) \frac{(x-\xi)\bar{i} + (z-\zeta)\bar{k}}{(x-\xi)^2 + (z-\zeta)^2} ds \\ + \frac{1}{2\pi} \oint_g \gamma_g(s) \frac{(z-\zeta)\bar{i} - (x-\xi)\bar{k}}{(x-\xi)^2 + (z-\zeta)^2} ds \end{aligned} \quad (10)$$

$$\begin{aligned}
& + \frac{1}{2\pi} \iint G(\xi, \zeta) \frac{(x-\xi) \bar{i} + (z-\zeta) \bar{k}}{(x-\xi)^2 + (z-\zeta)^2} d\xi d\zeta \\
& + \frac{1}{2\pi} \oint_S q_S(s) \frac{(x-\xi) \bar{i} + (z-\zeta) \bar{k}}{(x-\xi)^2 + (z-\zeta)^2} ds
\end{aligned}$$

where  $S$  is shock surface,  $q$  and  $\gamma$  are surface source and vortex distribution; respectively.

In Eq. (10), first integral is the contribution of the body thickness; second integral is the contribution of lifting or lifting and thickness or thickness only; third integral is the contribution due to the compressibility; while last integral is contribution due to shock.

Not all of the first and second integral terms in Eq. (10) are necessarily included in the calculation of the velocity field. For symmetric flows, either first integral or second integral can be used; while for asymmetric flows, either second integral or both integrals should be used.

Note that the integrand of the volume integral of Eq. (10) decreases rapidly with increasing distance not only because of the factor  $1/((x-\xi)^2 + (z-\zeta)^2)$  but also because  $G$  diminishes rapidly with increasing distance. Consequently, for computational purposes, the volume integral needs to be addressed only within the immediate vicinity of the body.

The reader should notice that the difference between the present formulation and the formulations given by Sinclair [35] and by Tseng and Morino [36]. The present formulation is based on the velocity field in which the source term  $G$  contains first order derivatives of density only, and the normal velocity is discontinuous across the shock. The Sinclair and Tseng and Morino formulations are both based on the velocity potential in which the source term  $G$  contains first- and second-order derivatives of the velocity

potential and the velocity potential is continuous across the shock. The present formulation has two advantages over the velocity-potential formulation: (1) only first-order derivatives need to be calculated by finite differencing, and (2) one does not need to calculate derivatives of the velocity potential in order to detect the shock formation since the velocity field is calculated directly in the present formulation.

### (c) Shock-capturing and Shock-fitting Technique

Before switching to the next section for numerical procedure it is worth discussing the last integral term of Eq. (10).

For treating transonic flows, we consider two techniques - shock-capturing and shock-fitting techniques. Although these techniques are well known, we examine here their application to the integral equation formulation.

In the shock-fitting technique, the contribution of the shock to the velocity field is represented by an explicit surface - integral term, the last term of Eq. (10), and the shock strength  $q_s$  is given by the normal velocity increment across it. Thus

$$q_s = - (V_{1n} - V_{2n}) \quad (11)$$

But in the shock-capturing technique, the last term of Eq. (10) is not necessarily included, since the volume integral itself implicitly includes the shock surface contribution [32].

Therefore, for shock-capturing technique Eq. (10) becomes,

$$\begin{aligned} \bar{V}(x, z) \equiv u \bar{i} + w \bar{k} = \bar{e}_\infty + \frac{1}{2\pi} \oint_g q_g(s) \frac{(x-\xi) \bar{i} + (z-\zeta) \bar{k}}{(x-\xi)^2 + (z-\zeta)^2} ds \\ + \frac{1}{2\pi} \oint_g \gamma_g(s) \frac{(z-\zeta) \bar{i} - (x-\xi) \bar{k}}{(x-\xi)^2 + (z-\zeta)^2} ds \end{aligned} \quad (12)$$

$$+ \frac{1}{2\pi} \iint G(\xi, \zeta) \frac{(x-\xi) \bar{i} + (z-\zeta) \bar{k}}{(x-\xi)^2 + (z-\zeta)^2} d\xi d\zeta$$

We will use both shock-capturing and shock-fitting techniques for present work.

#### 4. SOLUTION PROCEDURE

The whole solution procedure will be described by three parts: (i) discretization of equations, (ii) iterative procedure for subcritical flows, and (iii) treatment of critical flows.

##### (i) Discretization of Equations

Eq. (12) expresses the solution to the potential equation, Eq. (5), as the sum of four terms, the first three terms are the standard panel method terms and the last term is a volume integral in the field described above. The airfoil surface is divided by a number of straight panels with linear source and/or vortex distribution. The field is divided into a number of rectangular meshes except at the airfoil surface where trapezoidal elements are used. The value of  $G$  is taken to be constant over each mesh. Figure 1 shows the airfoil panels and field meshes. After discretization of equations, the integral equation solution, Eq. (12), becomes

$$\begin{aligned} \bar{V}(x, z) = \bar{e}_{\infty} + \frac{1}{2\pi} \sum_{k=1}^N \oint q_{gk} \frac{(x-\xi) \bar{i} + (z-\zeta) \bar{k}}{(x-\xi)^2 + (z-\zeta)^2} ds_k \\ + \frac{1}{2\pi} \sum_{k=1}^N \oint \gamma_{gk} \frac{(z-\zeta) \bar{i} - (x-\xi) \bar{k}}{(x-\xi)^2 + (z-\zeta)^2} ds_k \end{aligned} \quad (13)$$

$$+ \frac{1}{2\pi} \sum_{i=1}^{IM} \sum_{k=1}^{JM} G_{ij} \iint_{A_{ij}} \frac{(x-\xi) \bar{i} + (z-\zeta) \bar{k}}{(x-\xi)^2 + (z-\zeta)^2} d\xi d\zeta$$

where N is total number of surface panels, IM x JM the total number of field meshes,  $A_{ij}$  the area of each field meshes.

#### (ii) Iterative Procedure for Subcritical Flows

The main difference between standard panel methods and integral equation methods (or field panel methods) is due to the volume integral term in Eq. (13). This term is a non-linear term and therefore unlike the standard panel method, the solution cannot be obtained directly and an iterative procedure is necessary. For simplicity, we discuss the iterative procedure for subcritical flows first.

The iterative cycle is described below.

##### Step 1

A standard panel method calculation, with  $G = 0$ , is employed to get  $q_g$  or  $\gamma_g$ .

##### Step 2

Calculate  $G$  for each mesh by using the linear compressibility,  $G = M_\infty^2 u_x$ , where  $u_x$  is calculated from the results of Step 1.

##### Step 3

Enforce the no-penetration condition and Kutta condition to get new  $q_g$  or  $\gamma_g$ . In this step, the contribution of  $G$  is included.

##### Step 4

Calculate  $G$  by using non-linear compressibility, Eq. (6). In this step, we first calculate  $\Phi_x$  and  $\Phi_z$  by using Eq. (13), compute density ( $\rho$ ) by Eq. (4) and  $\rho_x$  and  $\rho_z$  are computed by central differencing for subcritical flows.

Step 5

Enforce no-penetration condition and kutta condition again to solve for new  $q_g$  or  $\gamma_g$ .

Step 6

Repeat Steps 4 and 5 until  $q_g$  or  $\gamma_g$  and  $G$  converge. In each step, the pressure coefficient is computed by

$$C_p = \frac{2}{\gamma M_\infty^2} \left\{ \left[ 1 + \frac{\gamma-1}{2} M_\infty^2 (1-V^2) \right]^{\frac{\gamma}{\gamma-1}} - 1 \right\} \quad (14)$$

where  $V = |\vec{V}|$ . Note that when calculating the pressure on the surface, the self-induced velocity must be treated carefully.

## (iii) Treatment of Critical Flows

Several key points have been used for treating transonic flows with shocks:

(1) For the critical flow with shocks, a mixed type finite difference must be applied to calculate  $\rho_x$  and  $\rho_z$ ; consistent with the mixed nature of transonic flow. The local Mach number is calculated by

$$M = VM_\infty / \rho^{\frac{\gamma-1}{2}} \quad (15)$$

(2) The conditions behind the shock are determined by using the Rankine-Hugoniot relations:

$$V_{2n} = \frac{(\gamma-1) M_{1n}^2 + 2}{(\gamma+1) M_{1n}^2} V_{1n} \quad (16.a)$$

$$V_{2t} = V_{1t} \quad (16.b)$$

$$\rho_2 = \frac{(\gamma+1) M_{1n}^2}{(\gamma-1) M_{1n}^2 + 2} \rho_1 \quad (16.c)$$

(3) Shock panels are introduced in order to sharpen the discontinuity in flow properties. The panels are added after several iterations when the location of the shock is fixed. The orientation of the shock panels is determined by Rankine-Hugoniot equation.

$$\beta = \sin^{-1} \left[ \frac{1.2 \sin(\beta) \sin(\theta)}{\cos(\beta - \theta)} + \frac{1}{M_1^2} \right]^{1/2} \quad (17)$$

where  $\beta$  is the shock angle and  $\theta$  is the relative direction of the flow behind the shock to that ahead of the shock. The strength of shock is give by

$$G\epsilon = - (V_{1n} - V_{2n}) = - \frac{2 V_{1n}}{\gamma + 1} \cdot \left( 1 - \frac{1}{M_{1n}^2} \right), M_{1n} > 1.0 \quad (18)$$

## 5. NUMERICAL EXAMPLES

A scalar program has been developed to implement the solution procedure of the shock capturing-shock fitting technique. To prove the concept and verify the algorithm, the code is applied to NACA0012 airfoil at different Mach numbers and different angles of attack.

### CASE A Subcritical Flows

Fig. 2 shows a comparison of the present results with experimental data for incompressible flow at  $\alpha = 0^\circ$ . A total of 140 panels is used for whole calculations over upper and lower airfoil surfaces. Two different modeling options, source panel modeling and vortex panel modeling, are applied respectively. The comparison shows that the vortex panel modeling is better than the source panel modeling.

Fig. 3a through Fig. 3c are for the case of  $\alpha = 0$ ,  $M_\infty = 0.72$ . Fig. 3a gives the comparison of the results of the two different modeling methods with Euler's solution, and it is again shown that the vortex panel modeling is better than the source panel modeling. Fig. 3b shows the effect of the size of computational domain, while Fig. 3c shows that the present solution compares well with Euler's solution.

The next case illustrated is a lifting case with  $\alpha = 2^\circ$  and  $M_\infty = 0.63$ . Fig. 4a shows the effect of the size of the computational domain and Fig. 4b shows the comparison of present solution with finite difference solution of the full potential equation.

#### CASE B Critical Flows

Fig. 5a shows the present results compared with the experimental data and Garabedian's finite difference solution. The computational domain used is  $2c \times 1.5c$  as shown in Fig. 1. The properties behind the shock are calculated using Rankine-Hugoniot relations as given by Eqs. (16.a) - (16.c). The results show that the present integral solution method is capable of capturing a sharp shock. The location and strength of the shock calculated here are in a very good agreement with the experimental data and the finite difference solution. Fig. 5b shows the effect of shock panels on the shock strength. The comparison shows that the shock panels are effective for sharpening the shock. Fig. 6 shows the lifting case result for  $\alpha = 2^\circ$ ,  $M_\infty = .75$ . The comparison shows good agreement.

## 6. CONCLUDING REMARKS

The standard panel method has been extended to the treatment of transonic flows. The results presented here show that the method is capable of capturing sharp shocks. The location and strength of shocks are in a very good agreement with the experimental data and finite difference solutions. Introduction of shock panels sharpens the shock with relatively coarse grids. Presently, the method is applied to unsteady transonic flow cases where the unsteady density term is treated as another volume integral term. A time-splitting finite difference scheme is used to step the equation in time while the integral solution is used to compute the spatial variation. The full length paper will include transonic flow cases in pitching motion.

## REFERENCES

1. Hess, J. L. and Smith, A. M., "Calculation of Non-lifting Potential Flow about Arbitrary Three-Dimensional Bodies," Progress in Aeronautical Science, edited by D. Kuchemann, 1967, 8, 1-138.
2. Murman, E. M. and Cole, J. D., "Calculation of Plane Steady Transonic Flows," AIAA Journal, Vol. 9, No. 1, 1971, pp. 114-121.
3. Ballhaus, W. F. and Bailey, F. R., "Numerical Calculation of Transonic Flow about Swept Wings," AIAA Paper 72-677, June 1972.
4. Bailey, F. R. and Ballhaus, W. F., "Relaxation Methods for Transonic Flow about Wing-Cylinder Combinations and Lifting Swept Wings," Third International Conference on Numerical Methods in Fluid Dynamics, Paris, July, 1972.
5. Steger, J. L. and Lomax, H., "Transonic Flow about Two-Dimensional Airfoils by Relaxation Procedures," AIAA Journal, Vol. 10, No. 1, 1972, pp. 49-54.
6. Garabedian, P. R. and Korn, D., "Analysis of Transonic Airfoils," Comm. Pure Appl. Math., Vol. 24, 1972, pp. 841-851.
7. Jameson, A., "Iterative Solution of Transonic Flows over Airfoils and Wings, Including Flow at Mach 1," Comm. Pure Appl. Math., Vol. 27, 1974, pp. 283-309.
8. Jameson, A., "Transonic Potential Flow Calculation Using Conservation Form," Proceedings of the AIAA Second Computational Fluid Dynamics Conference, Hartford, Conn., June, 1975, pp. 148-161.
9. Jameson, A. and Caughey, D. A., "Finite Volume Method for Transonic Potential Calculations," Proceedings of AIAA Third Computational Fluid Dynamics Conference, June 1977, AIAA, New York, 1977, pp. 33-54.
10. Caughey, D. A. and Jameson, A., "Numerical Calculation of Transonic Potential Flow about Wing-Body Combinations," AIAA Journal, Vol. 17, No. 2, 1979, pp. 175-181.
11. Jameson, A., "Transonic Airfoil Calculations Using the Euler Equation," in Numerical Methods in Aeronautical Fluid Dynamics, Edited by P. L. Roe, Academic Press, 1982, pp. 289-308.
12. Rebach, C., "Calculation of Flow Around Zero-Thickness Wings with Evolute Vortex Sheets," NASA TT F-15, 183, 1973.
13. Kandil, O. A., Mook, D. T. and Nayfeh, A. H., "Nonlinear Prediction of the Aerodynamic Loads on Lifting Surfaces," Journal of Aircraft, Vol. 12, No. 1, 1976, pp. 22-28.

14. Kandil, O. A., Mook, D. T. and Nayfeh, A. H., "A Numerical Technique for Computing Subsonic Flow Past Three-Dimensional Canard-Wing Configurations with Edge Separation," AIAA Paper 79-0282, January 1979.
15. Kandil, O. A. and Balakrishnan, L., "Recent Improvements in the Predictions of the Leading- and Trailing-Edge Vortex Cores of Delta Wings," AIAA Paper 81-1263, June 1981.
16. Johnson, F. T., Tinoco, E. N., Lu, P. and Epton, M. A., "Recent Advances in the Solution of Three-Dimensional Flows Over Wings with Leading Edge Vortex Separation," AIAA Paper 77-0282, January 1977.
17. Hoeijmakers, H.W.M. and Vaatstra, W., "A Higher-Order Panel Method Applied to Vortex Sheet Roll-Up," AIAA Paper 82-0096, January 1982.
18. Luckring, J. M., Schoonover, W. E., Jr. and Frank, N. T., "Recent Advances in Applying Free Vortex Sheet Theory for the Estimation of Vortex Flow Aerodynamics," AIAA Paper 82-0095, 1982.
19. Lamar, J. E. and Campbell, J. F., "Recent Studies at NASA- Langley of Vortical Flows Interacting with Neighboring Surfaces," AGARD CP No. 342, April 1983.
20. Hoeijmakers, H. M., "Computational Vortex Flow Aerodynamic," AGARD CP No. 342, April 1983.
21. Kandil, O. A., Chu, L. C. and Yates, E. C., Jr. "Hybrid Vortex Method for Lifting Surfaces with Free Vortex Flow," AIAA Paper 80-0070, January 1980.
22. Kandil, O. A., Chu, L. and Turead, T., "A Nonlinear Hybrid Vortex Method for Wings at Large Angle of Attack,": AIAA Paper 82-0351, January 1982.
23. Suciu, E. O. and Morino, L., "Nonlinear Steady Incompressible Lifting Surface Analysis with Wake Roll-Up," AIAA Journal, Vol. 15, No. 1, 1977, pp. 54-58.
24. Luu, T. S., Goulmy, G. and Dulieu, A., "Calcul de l'ecoulement transsonique autour d'un profil en admettant la loi de compressibilite exacte," Association technique Maritime et Aeronautique Session, 1972.
25. Stricker, R., "On an Integral Equation Method for Calculation of the Fully Non-linear Potential Flow about Arbitrary Section Shapes," Paper Presented at the Euromech Colloquium 75 on the Calculation of Flow Fields by Means of Panel Methods, Rhode/Braunschweig, May 1976.
26. Oswatitsch, K., "Die Geschwindigkeitsverteilung ab Symmetrische Profilen beim auftreten lokaler Überschallgebiete," Acta Physica Austriaca Vol. 4, 1950, pp. 228-271.

27. Spreiter, J. R. and Alksne, A. Y., "Theoretical Prediction of Pressure distributions on Non-Lifting Airfoils at High Subsonic Speeds," NACA Rpt. 1217, 1955.
28. Norstrud, H., "High Speed Flow Past Wings," NASA Cr-2246, 1973.
29. Crown, J. C., "Calculation of Transonic Flow over Thick Airfoils by Integral Methods," AIAA Journal, Vol. 6, No. 3, 1968, pp. 413-423.
30. Nixon, D., "Transonic Flow Around Symmetric Aerofoils at Zero Incidence," Journal of Aircraft, Vol. 11, No. 2, 1974, pp. 122-124.
31. Piers, W. J. and Sloof, J. W., "Calculation of Transonic Flow by Means of a Shock-Capturing Field Panel Method," AIAA Paper 79-1459, 1979.
32. Kandil, O. A. and Yates, E. C., Jr., "Computation of Transonic Vortex Flow Past Delta Wings - Integral Equation Approach," AIAA Paper 85-1582, 1985, also AIAA Journal, Vol. 24, No. 11, 1986, pp. 1729-1736.
33. Oskam, B., "Transonic Panel Method for the Full Potential Equation Applied to Multicomponent Airfoils," AIAA Journal, Vol. 23, No. 9, 1985, pp. 1327-1334.
34. Erickson, L. L. and Strande, S. M., "A Theoretical Basis for Extending Surface- Paneling Methods to Transonic Flow," AIAA Journal, Vol. 23, No. 12, 1985, pp. 1860-1867.
35. Sinclair, P. M., "An Exact Integral (Field Panel) Method for the Calculation of Two-Dimensional Transonic Potential Flow Around Complex Configurations," Aeronautical Journal, June/July 1986, pp. 227-236.
36. Tseng, K. and Morino, L., "Nonlinear Green's Function Methods for Unsteady Transonic Flows," in Transonic Aerodynamics, edited by D. Nixon, AIAA, New York, 1982, pp. 565-603.
37. Abbott, I. H. and von Doenhoff, A. E., "Theory of Wing Sections," Dover Publications, Inc., New York, 1959, pp. 321.
38. Sells, C.C.L., "Plane Subcritical Flow Past a Lifting Airfoil," Proceedings of the Royal Society, London, Vol. 308 (Series A), 1968, pp. 377-401.
39. Garabedian, P., Korn, D. G. and Jameson, A., "Supercritical Wing Sections," Lecture notes in economic and mathematical systems, No. 66, 1972.
40. Hafez, M., "Perturbation of Transonic Flow with Shocks," in Numerical and Physical Aspects of Aerodynamic Flows edited by Tuncer Cebeci, Springer-Verlag, New York, Heidelberg, Berlin, 1982, pp. 421-438.
41. Hall, M. G., "Transonic Flows," IMA; Controller HMSO London, 1975.
42. United Aircraft Corp., Sikorsky Aircraft Division, "Two-Dimensional Wind Tunnel Tests of an H-34 Main Rotor Airfoil Section," TRECTR 60-53, 1960.




Fig. 1 Computational mesh, NACA 0012  
aerofoil, 64 x 60 field mesh.




Fig. 2 NACA 0012 aerofoil,  $M_\infty = 0.0$ ,  $\alpha = 0.0$ .




Fig. 3a NACA 0012 aerofoil,  $M_\infty = .72$ ,  $\alpha = 0.0$ , computational domain:  $2 \times 1.5$ .




Fig. 3b NACA 0012 aerofoil,  $M_\infty = .72$ ,  $\alpha = 0.0$ , with vortex panels, effect of the size of the computational domain.




Fig. 3c NACA 0012 aerofoil,  $M_\infty = .72$ ,  $\alpha = 0.0$ ,  
with vortex panels, computational  
domain: 3 x 2.5.




Fig. 4a MACA 0012 aerofoil,  $M_\infty = .63$ ,  $\alpha = 2.0$ , with vortex panels, effect of the size of the computational domain.




Fig. 4b NACA 0012 aerofoil,  $M_\infty = .63$ ,  $\alpha = 2.0$ ,  
with vortex panels, computational  
domain:  $3 \times 2.5$ .




Fig. 5a NACA 0012 aerofoil,  $M_\infty = .80$ ,  
 $\alpha = 0.0$ , with vortex panels,  
 computational domain:  $2 \times 1.5$ .




Fig. 5b NACA 0012 aerofoil,  $M_\infty = .80$ ,  
 $\alpha = 0.0$ , with vortex panels,  
 computational domain:  $2 \times 1.5$ ,  
 effect of shock panels.




Fig. 6 NACA 0012 aerofoil,  $M_\infty = .75$ ,  $\alpha = 2.0$ ,  
 with vortex panels, the computational  
 domain:  $2 \times 1.5$ .